

# K-WTEH SERIE ONE 0 DRS

Service units, »ONE« Series, without pressure switch



Ieejas spiediens  
Max. 10 bar  
Temperatūras diapazons  
-10 °C to +50 °C  
Darba vides  
Saspiests gaiss  
Aizsardzības veids  
IP 65  
Caurplūde  
At 6,3 bar and  $\Delta p = 1$  bar  
Darba spiediens  
0.5 - 8 bar  
Spiediena slēdzis  
Changeover contact  
Poru attālums filtra elementā  
20  $\mu$ m  
Caurplūdes vērtības mērijums  
At 6,3 bar and  $\Delta p = 1$  bar

## Apraksts

Multifunctional service unit with 6 or 7 functions in a single device: 3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valve and optional: pressure switch. This combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market! Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Savienojums	Caurpl_de nom. l/min	A mm	B	C mm	Spriegums
K- 07 25 13 79	G 1/4"	2400	165.5	144.0 mm	35.0	24 V DC (for valves and pressure switch)
K- 07 25 13 80	G 3/8"	3300	165.5	144.0 mm	35.0	24 V DC (for valves and pressure switch)
K- 07 25 13 81	G 1/2"	4000	165.5	144.0 mm	35.0	24 V DC (for valves and pressure switch)