


K-WTST SAFETY BK SCHA AN DR

HANSA

SAFETY service unit sets, comprising a ball valve with silencer, start-up valve and pressure regulator



Ieejas spiediens
2.5 - 16 bar
Izejas spiediens
0.5 - 8 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Filtra elements
Cellpor (PE) 5 μm
Korpuss
Material: Grivory® (PA 66)
Membrāna
NBR
Pieslēguma vītne
Material: Die-cast zinc
Tvertne
Polycarbonate (with bayonet lock) and bowl guard
Iekšējā gaisa patēriņš
Max. 1.5 l/min (depending on secondary pressure)
Caurplūdes vērtības mērījums
At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar
Atgaisošanas pieslēgums Lodveida krāns
Silencer

Apraksts

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītne	Regulēšanas diapazons	Caurplūde nom. l/min	A mm	B	C mm
K- 07 25 15 20	G 1/4	2.5 - 8 bar	2000	156.0	128.5 mm	95.5
K- 07 25 15 21	G 3/8	2.5 - 8 bar	2000	156.0	128.5 mm	95.5
K- 07 25 15 22	G 3/8	2.5 - 8 bar	4300	189.0	149.5 mm	110.0
K- 07 25 15 23	G 1/2	2.5 - 8 bar	4300	189.0	149.5 mm	110.0
K- 07 25 15 24	G 3/4	2.5 - 8 bar	10000	255.0	191.0 mm	137.0
K- 07 25 15 25	G 1	2.5 - 8 bar	10000	255.0	191.0 mm	137.0