


K-WTST SAFETY BK SCHA AN DR

HANSA

SAFETY service unit sets, comprising a ball valve with silencer, start-up valve and pressure regulator



Ieejas spiediens
2.5 - 16 bar
Izejas spiediens
0.5 - 8 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Filtra elements
Cellpor (PE) 5 μm
Korpuss
Material: Grivory® (PA 66)
Membrāna
NBR
Pieslēguma vītne
Material: Die-cast zinc
Tvertne
Polycarbonate (with bayonet lock) and bowl guard
Iekšējā gaisa patēriņš
Max. 1.5 l/min (depending on secondary pressure)
Caurplūdes vērtības mērījums
At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar
Atgaisošanas pieslēgums Lodveida krāns
Silencer

Apraksts

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītne	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 15 20	G 1/4	2.5 - 8 bar	2000	156.0	128.5 mm	95.5
K- 07 25 15 21	G 3/8	2.5 - 8 bar	2000	156.0	128.5 mm	95.5
K- 07 25 15 22	G 3/8	2.5 - 8 bar	4300	189.0	149.5 mm	110.0
K- 07 25 15 23	G 1/2	2.5 - 8 bar	4300	189.0	149.5 mm	110.0
K- 07 25 15 24	G 3/4	2.5 - 8 bar	10000	255.0	191.0 mm	137.0
K- 07 25 15 25	G 1	2.5 - 8 bar	10000	255.0	191.0 mm	137.0