

K-WTST SAFETY BK SCHA AN FILR HANSA

SAFETY service unit sets, comprising a ball valve with silencer, start-up valve and filter regulator



Ieejas spiediens
2.5 - 16 bar
Izejas spiediens
0.5 - 8 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Filtra elements
Cellpor (PE) 5 μm
Korpuss
Material: Grivory® (PA 66)
Membrāna
NBR
Pieslēguma vītne
Material: Die-cast zinc
Tvertne
Polycarbonate (with bayonet lock) and bowl guard
Iekšējā gaisa patēriņš
Max. 1.5 l/min (depending on secondary pressure)
Caurplūdes vērtības mērījums
At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar
Atgaisošanas pieslēgums Lodveida krāns
Silencer

Apraksts

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	Kondensāta notece
K- 07 25 15 26	G 1/4	2000	156.0	225.0 mm	95.5	Semi
K- 07 25 15 27	G 3/8	2000	156.0	225.0 mm	95.5	Semi
K- 07 25 15 28	G 3/8	4300	189.0	257.0 mm	110.0	Semi
K- 07 25 15 29	G 1/2	4300	189.0	257.0 mm	110.0	Semi
K- 07 25 15 30	G 3/4	10000	255.0	329.0 mm	137.0	Semi
K- 07 25 15 31	G 1	10000	255.0	329.0 mm	137.0	Semi
K- 07 25 15 32	G 1/4	2000	156.0	243.0 mm	95.5	Auto
K- 07 25 15 33	G 3/8	2000	156.0	243.0 mm	95.5	Auto
K- 07 25 15 34	G 3/8	4300	189.0	274.0 mm	110.0	Auto
K- 07 25 15 35	G 1/2	4300	189.0	274.0 mm	110.0	Auto
K- 07 25 15 36	G 3/4	10000	255.0	343.0 mm	137.0	Auto
K- 07 25 15 37	G 1	10000	255.0	343.0 mm	137.0	Auto