

K-WTST SAFETY BK SCHA AN

HANSA

SAFETY service unit sets, comprising a ball valve with silencer, start-up valve and 2-piece service unit



Ieejas spiediens
2.5 - 16 bar
Izejas spiediens
0.5 - 8 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Filtra elements
Cellpor (PE) 5 μm
Korpuss
Material: Grivory® (PA 66)
Membrāna
NBR
Pieslēguma vītne
Material: Die-cast zinc
Tvertne
Polycarbonate (with bayonet lock) and bowl guard
Iekšējā gaisa patēriņš
Max. 1.5 l/min (depending on secondary pressure)
Caurplūdes vērtības mērījums
At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar
Atgaisošanas pieslēgums Lodveida krāns
Silencer

Apraksts

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Caurpl_de nom. l/min | A mm | B | C mm | Kondensāta notece |
|----------------|--------|-------------------------|---------|----------|---------|-------------------|
| K- 07 25 15 38 | G 1/4 | 1750 | 208.0 | 225.0 mm | 95.5 | Semi |
| K- 07 25 15 39 | G 3/8 | 1750 | 208.0 | 225.0 mm | 95.5 | Semi |
| K- 07 25 15 40 | G 3/8 | 3500 | 252.0 | 257.0 mm | 110.0 | Semi |
| K- 07 25 15 41 | G 1/2 | 3500 | 252.0 | 257.0 mm | 110.0 | Semi |
| K- 07 25 15 42 | G 3/4 | 10000 | 340.0 | 329.0 mm | 137.0 | Semi |
| K- 07 25 15 43 | G 1 | 10000 | 340.0 | 329.0 mm | 137.0 | Semi |
| K- 07 25 15 44 | G 1/4 | 1750 | 208.0 | 243.0 mm | 95.5 | Auto |
| K- 07 25 15 45 | G 3/8 | 1750 | 208.0 | 243.0 mm | 95.5 | Auto |
| K- 07 25 15 46 | G 3/8 | 3500 | 252.0 | 274.0 mm | 110.0 | Auto |
| K- 07 25 15 47 | G 1/2 | 3500 | 252.0 | 274.0 mm | 110.0 | Auto |
| K- 07 25 15 48 | G 3/4 | 10000 | 340.0 | 343.0 mm | 137.0 | Auto |
| K- 07 25 15 49 | G 1 | 10000 | 340.0 | 343.0 mm | 137.0 | Auto |