

K-WTST SAFETY BKR SCHA AN DR MULTI

SAFETY service unit sets, comprising a ball valve with silencer, start-up valve and pressure regulator with lock cylinder



Ieejas spiediens
2 - 16 bar
Izejas spiediens
0.5 - 10 bar
Temperatūras diapazons
Max. 60 °C
Darba vides
Saspiests gaiss
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Atsperes korpuss
POM
Filtra elements
Cellpor (PE) 5 μm
Korpuss
Die-cast zinc
Membrāna
NBR
Tvertne
Polycarbonate (with bayonet lock) and bowl guard
Drain valve
Semi-automatic
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Atgaisošanas pieslēgums Lodveida krāns
Silencer

Apraksts

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Produkts

| Apzīmējums | Vītnes | Regulēšanas diapazons | Caurpl_de nom. l/min | A mm | B | C mm |
|----------------|--------|-----------------------|-------------------------|---------|----------|---------|
| K- 07 25 15 11 | G 1/4 | 2 - 10 bar | 1000 | 128.0 | 137.8 mm | 94.0 |
| K- 07 25 15 12 | G 1/2 | 2 - 10 bar | 4000 | 189.0 | 200.8 mm | 122.0 |
| K- 07 25 15 13 | G 1 | 2 - 10 bar | 12000 | 241.7 | 282.8 mm | 157.0 |