

# K-WTST SAFETY BKR SCHA AN FILR MULT

SAFETY service unit sets, comprising a ball valve with silencer, start-up valve and filter regulator with lock cylinder



Ieejas spiediens  
2 - 16 bar  
Izejas spiediens  
0.5 - 10 bar  
Temperatūras diapazons  
Max. 60 °C  
Darba vides  
Saspiests gaiss  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Atsperes korpuss  
POM  
Filtra elements  
Cellpor (PE) 5  $\mu\text{m}$   
Korpuss  
Die-cast zinc  
Membrāna  
NBR  
Tvertne  
Polycarbonate (with bayonet lock) and bowl guard  
Drain valve  
Semi-automatic  
Caurplūdes vērtības mērījums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Atgaisošanas pieslēgums Lodveida krāns  
Silencer

## Apraksts

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

## Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	Kondensāta notece
K- 07 25 15 14	G 1/4	1000	219.1	137.8 mm	94.0	Semi-automatic
K- 07 25 15 15	G 1/2	4000	269.3	200.8 mm	122.0	Semi-automatic
K- 07 25 15 16	G 1	12000	410.8	282.8 mm	157.0	Semi-automatic