

# K-FI AK KOH METALLBEHAE MULTIFIX MI

Activated carbon filters with metal bowl



Ieejas spiediens  
Max. 16 bar  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
FA at P1 = 6 bar and pressure drop  $\Delta p = 0.2$  bar  
Blīvējums  
NBR  
Filtra ieliktnis  
Activated carbon-POM  
Korpuss  
Die-cast zinc  
Drain valve  
Semi-automatic  
Atlikusi eļļa  
0.005 mg/m<sup>3</sup>  
Caurplūdes vērtības mērijums  
FA at P1 = 6 bar and pressure drop  $\Delta p = 0.2$  bar

## Apraksts

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | Caurpl_de nom.<br>l/min | A<br>mm | B       | C<br>mm | D<br>mm | DN | Tipizmērs |
|----------------|--------|-------------------------|---------|---------|---------|---------|----|-----------|
| K- 07 25 10 46 | G 1/8  | 310                     | 40.0    | 97.3 mm | 12.3    | 85.0    | 5  | 0         |