

K-FI AK KOH METALLBEHAEL MULTIFIX

Activated carbon filters with metal bowl



Ieejas spiediens
Max. 16 bar
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
FA at P1 = 6 bar and $\Delta p = 0.2$ bar
Blīvējums
NBR
Filtra ieliktnis
Activated carbon-POM
Korpuss
Die-cast zinc
Drain valve
Semi-automatic
Atlikusi eļļa
0.005 mg/m³
Caurplūdes vērtības mērijums
FA at P1 = 6 bar and $\Delta p = 0.2$ bar

Apraksts

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Caurpl_de nom. l/min | A mm | B | C mm | D mm | DN | Tipizmērs |
|----------------|--------|-------------------------|---------|----------|---------|---------|----|-----------|
| K- 07 25 10 49 | G 1/4 | 380 | 47.8 | 137.0 mm | 27.0 | 110.0 | 6 | 1 |
| K- 07 25 10 52 | G 1/2 | 1500 | 68.8 | 168.2 mm | 34.5 | 133.7 | 15 | 2 |