

K-FI AK KOH METALLBEHAEL SI VARIOBL

Activated carbon filters with metal bowl incl. sight glass



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)
Vielas temperatūra
max. 50 °C
Caurplūde
At P1 = 7 bar and pressure drop $\Delta p = 0,1$ bar
Gaisa kvalitāte ISO 85731
Class 1 dirt, class 1 oil
Atlikusi eļļa
0,003 mg/m³
Caurplūdes vērtības mērijums
At P1 = 7 bar and pressure drop $\Delta p = 0,1$ bar

Apraksts

The activated carbon filter absorbs oil vapour from the compressed air. The entering compressed air needs to be dry and free of contaminants (an upstream microfilter is strongly recommended).

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Caurpl_de nom. l/min | A mm | B | C mm |
|----------------|--------|-------------------------|---------|----------|---------|
| K- 07 25 23 07 | G 1/4 | 800 | 48.0 | 142,0 mm | 22.0 |
| K- 07 25 23 08 | G 3/8 | 1000 | 48.0 | 142,0 mm | 22.0 |
| K- 07 25 23 09 | G 1/2 | 1200 | 70.0 | 193,0 mm | 26.0 |
| K- 07 25 23 10 | G 3/4 | 1300 | 70.0 | 193,0 mm | 26.0 |
| K- 07 25 23 11 | G 1 | 1300 | 124.0 | 193,0 mm | 26.0 |