

# K-FI AK KOH METALLBEHAEL SI VARIOBL

Activated carbon filters with metal bowl incl. sight glass



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)  
Vides temperatūra  
Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)  
Vielas temperatūra  
max. 50 °C  
Caurplūde  
At P1 = 7 bar and pressure drop  $\Delta p = 0,1$  bar  
Gaisa kvalitāte ISO 85731  
Class 1 dirt, class 1 oil  
Atlikusi eļļa  
0,003 mg/m<sup>3</sup>  
Caurplūdes vērtības mērijums  
At P1 = 7 bar and pressure drop  $\Delta p = 0,1$  bar

## Apraksts

The activated carbon filter absorbs oil vapour from the compressed air. The entering compressed air needs to be dry and free of contaminants (an upstream microfilter is strongly recommended).

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 23 07	G 1/4	800	48.0	142,0 mm	22.0
K- 07 25 23 08	G 3/8	1000	48.0	142,0 mm	22.0
K- 07 25 23 09	G 1/2	1200	70.0	193,0 mm	26.0
K- 07 25 23 10	G 3/4	1300	70.0	193,0 mm	26.0
K- 07 25 23 11	G 1	1300	124.0	193,0 mm	26.0