

K-FI AK KOH PC-BEHAE SCHUTZK HANSA

Activated carbon filters



Ieejas spiediens
0 - 16 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P2 = 6 bar and pressure drop $\Delta p = 0.5$ bar
Aizsarggrozs
Polyamide
Filtra elements
Activated carbon
Korpuss
Material: Grivory® (PA 66)
Pieslēguma vītne
Material: Die-cast zinc
Tvertne
Polycarbonate (with bayonet lock)
Atlikusi eļļa
0.005 mg/m³, class 0 acc. to DIN ISO 8573-1
Caurplūdes vērtības mērijums
At P2 = 6 bar and pressure drop $\Delta p = 0.5$ bar

Apraksts

Activated carbon filters in modern design for compliance with strict compressed air purity requirements.
Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m³ from compressed air and gases.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 10 41	G 1/4	500	52.0	157.0 mm	34.0
K- 07 25 10 42	G 3/8	500	52.0	157.0 mm	34.0
K- 07 25 10 43	G 3/8	1600	63.0	183.0 mm	42.5
K- 07 25 10 44	G 1/2	1600	63.0	183.0 mm	42.5
K- 07 25 10 23	G 3/4	3000	85.0	240.5 mm	58.0
K- 07 25 10 24	G 1	3000	85.0	240.5 mm	58.0