

K-FI AK KOH PC-BEHAEL SI VARIOBLOC

Activated carbon filters with polycarbonate bowl and bowl guard



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)
Vielas temperatūra
max. 50 °C
Caurplūde
At P1 = 7 bar and pressure drop $\Delta p = 0,1$ bar
Gaisa kvalitāte ISO 85731
Class 1 dirt, class 1 oil
Atlikusi eļļa
0,003 mg/m³
Caurplūdes vērtības mērijums
At P1 = 7 bar and pressure drop $\Delta p = 0,1$ bar

Apraksts

The activated carbon filter absorbs oil vapour from the compressed air. The entering compressed air needs to be dry and free of contaminants (an upstream microfilter is strongly recommended).

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 23 12	G 1/4	800	48.0	142,0 mm	22.0
K- 07 25 23 13	G 3/8	1000	48.0	142,0 mm	22.0
K- 07 25 23 14	G 1/2	1200	70.0	193,0 mm	26.0
K- 07 25 23 15	G 3/4	1300	70.0	193,0 mm	26.0
K- 07 25 23 16	G 1	1300	124.0	193,0 mm	26.0