

# K-FI PC-BEHAELTER H ABLV STANDARD

Filters with polycarbonate bowl and semi-automatic drain valve



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Poru attālums filtra elementā  
5  $\mu\text{m}$  (Size 1 / Size 3), 40  $\mu\text{m}$  (Size 2 / Size 4), 60  $\mu\text{m}$  (Size 5)  
Korpuss  
Die-cast zinc, painted silver  
Caurplūdes vērtības mērijums  
At P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Centrifugal separators with a sintered filter element.

## Norādīt

G 2 1/2 and G 3 filters available on request

## Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	C mm	D mm	H mm	DN
K- 07 25 05 85	G 1/4	800	48.0	14.0	131.6	38.0	6
K- 07 25 05 88	G 3/8	800	48.0	14.0	131.6	38.0	6
K- 07 25 05 91	G 3/8	3100	70.0	16.0	145.7	50.0	10
K- 07 25 05 94	G 1/2	4000	79.0	18.0	168.4	50.0	15
K- 07 25 05 97	G 3/4	4000	102.0	26.5	169.9	50.0	20
K- 07 25 06 00	G 1	4000	90.0	26.5	169.9	50.0	25
K- 07 25 06 03	G 1 1/4	12500	125.0	36.5	243.4	105.0	40
K- 07 25 06 06	G 1 1/2	12500	125.0	36.5	243.4	105.0	45