



Ieejas spiediens
1.5 - 16 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P2 = 6 bar, pressure drop $\Delta p = 1$ bar
Filtra smalkums
5.00 μm
Blīvējums
NBR
Aizsarggrozs
Polyamide
Filtra elements
Cellpor (PE)
Korpuss
Material: Grivory® (PA 66)
Pieslēguma vītne
Material: Die-cast zinc
Tvertne
Polycarbonate (with bayonet lock)
Caurplūdes vērtības mērījums
At P2 = 6 bar, pressure drop $\Delta p = 1$ bar

Apraksts

Filters with excellent flow rates in modern design.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Filtra smalkums μm | Vītnes | Caurpl_de nom. l/min | A mm | B | C mm | Tipizmērs | Kondensāta notece |
|----------------|----------------------------------|--------|-------------------------|---------|----------|---------|-----------|-------------------|
| K- 07 25 05 64 | 5.00 | G 1/4 | 2000 | 52.0 | 164.0 mm | 34.0 | 1 | Semi |
| K- 07 25 05 65 | 5.00 | G 3/8 | 2000 | 52.0 | 164.0 mm | 34.0 | 1 | Semi |
| K- 07 25 05 66 | 5.00 | G 3/8 | 3500 | 63.0 | 189.5 mm | 42.5 | 2 | Semi |
| K- 07 25 05 67 | 5.00 | G 1/2 | 3500 | 63.0 | 189.5 mm | 42.5 | 2 | Semi |
| K- 07 25 05 60 | 5.00 | G 3/4 | 9000 | 85.0 | 250.0 mm | 58.0 | 4 | Semi |
| K- 07 25 05 61 | 5.00 | G 1 | 9000 | 85.0 | 250.0 mm | 58.0 | 4 | Semi |
| K- 07 25 05 68 | 5.00 | G 1/4 | 2000 | 52.0 | 181.0 mm | 34.0 | 1 | Auto |
| K- 07 25 05 69 | 5.00 | G 3/8 | 2000 | 52.0 | 181.0 mm | 34.0 | 1 | Auto |
| K- 07 25 05 70 | 5.00 | G 3/8 | 3500 | 63.0 | 206.0 mm | 42.5 | 2 | Auto |
| K- 07 25 05 71 | 5.00 | G 1/2 | 3500 | 63.0 | 206.0 mm | 42.5 | 2 | Auto |
| K- 07 25 05 62 | 5.00 | G 3/4 | 9000 | 85.0 | 264.0 mm | 58.0 | 4 | Auto |
| K- 07 25 05 63 | 5.00 | G 1 | 9000 | 85.0 | 264.0 mm | 58.0 | 4 | Auto |