

K-FI PC-BEHAELTER SCHUTZK MULTIFIX

Filters with polycarbonate bowl and bowl guard



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar
Poru attālums filtra elementā
5 μm (BG 1 / BG 2), 40 μm (BG 3)
Korpuss
Die-cast zinc, Aluminium for G 1 variant
Drain valve
Semi-automatic
Caurplūdes vērtības mērijums
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Centrifugal separator with a sintered filter element.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Caurpl_de nom. l/min | A mm | B | C mm | D mm | DN | Tipizmērs |
|----------------|--------|-------------------------|---------|----------|---------|---------|----|-----------|
| K- 07 25 00 48 | G 1/4 | 2100 | 47.8 | 152.1 mm | 27.0 | 125.1 | 6 | 1 |
| K- 07 25 00 51 | G 3/8 | 2100 | 47.8 | 152.1 mm | 27.0 | 125.1 | 10 | 1 |
| K- 07 25 00 54 | G 1/2 | 4000 | 68.8 | 181.8 mm | 34.5 | 147.3 | 15 | 2 |
| K- 07 25 00 57 | G 3/4 | 4000 | 68.8 | 181.8 mm | 34.5 | 147.3 | 20 | 2 |
| K- 07 25 00 60 | G 1 | 8000 | 100.0 | 305.8 mm | 52.0 | 253.8 | 25 | 3 |