

K-FI RUECKSPUEL M

DRUCKREGLER

Back-flushing filters with pressure regulator



Ieejas spiediens
Max. 16 bar
Vides temperatūra
+5 °C to +40 °C
Ūdens temperatūra maks.
30 °C
Ūdens temperatūra min.
5 °C
Poru attālums filtra elementā
90 μm (first filter element), 110 μm (second filter element)
Korpuss
Brass
Sietiņš
Impact-resistant plastic

Apraksts

Combined station for filtering and regulating the pressure of drinking and domestic water in addition to well, process and cooling water for once-through cooling systems, consisting of a diaphragm pressure regulator with a pressure-reduced single-seated valve and a back-flushing filter. The filter candle must be cleaned manually at regular intervals by back-flushing (flushing out dirt particles). Integrated back-flushing element with suction elements, back-flushing lever, wing lever for back-flushing element, hose connection for flushing water.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Ūdens temperatūra maks. °C	Ūdens temperatūra min. °C	Vītnes	Regulēšanas diapazons	Caurplūdes plūsmas koeficients m ³ /h	A mm	B	C m
K- 07 25 10 11	30	5	R 3/4	2 - 6 bar	3.0	79.7	213.0 mm	392.0
K- 07 25 10 12	30	5	R 1	2 - 6 bar	3.5	79.7	213.0 mm	392.0
K- 07 25 10 13	30	5	R 1 1/4	2 - 6 bar	4.0	79.7	213.0 mm	392.0