

# K-FI SPEZI PC-BEHAEL H K STANDARD

Special filters with polycarbonate bowl and bowl guard, with semi-automatic drain valve to G 1/2 and manual drain valve from G 3/4



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)  
Vides temperatūra  
Max. 50 °C  
Vielas temperatūra  
max. 50 °C  
Caurplūde  
At P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Iedarbības pakāpe  
99.999 %  
Poru attālums filtra elementā  
0.01  $\mu\text{m}$   
Korpuss  
Die-cast zinc, painted silver  
Caurplūdes vērtības mērījums  
At P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	C mm	D mm	H mm	DN
K- 07 25 10 75	G 1/4	380	48.0	14.0	131.6	38.0	6
K- 07 25 10 78	G 3/8	380	48.0	14.0	131.6	38.0	6
K- 07 25 10 80	G 3/8	720	70.0	16.0	145.7	50.0	10
K- 07 25 10 82	G 1/2	1250	79.0	18.0	168.4	50.0	15
K- 07 25 10 85	G 3/4	7000	133.0	36.0	206.0	134.0	20
K- 07 25 10 88	G 1	7000	133.0	36.0	206.0	120.0	25