

K-FI SPEZI PC-BEHAELTER H STANDAD

Special filters with polycarbonate bowl, with semi-automatic drain valve to G 1/2 and manual drain valve from G 3/4



Ieejas spiediens
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)
Vides temperatūra
Max. 50 °C
Vielas temperatūra
max. 50 °C
Caurplūde
At P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Iedarbības pakāpe
99.999 %
Poru attālums filtra elementā
0.01 μm
Korpuss
Die-cast zinc, painted silver
Caurplūdes vērtības mērījums
At P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Caurpl_de nom. l/min | A mm | C mm | D mm | H mm | DN |
|----------------|--------|-------------------------|---------|---------|---------|---------|----|
| K- 07 25 10 76 | G 3/8 | 380 | 48.0 | 14.0 | 131.6 | 38.0 | 6 |
| K- 07 25 10 83 | G 3/4 | 7000 | 133.0 | 36.0 | 206.0 | 134.0 | 20 |
| K- 07 25 10 86 | G 1 | 7000 | 133.0 | 36.0 | 206.0 | 120.0 | 25 |