

K-FI SPEZI PC-BEHAELTER H STANDAD

Special filters with polycarbonate bowl, with semi-automatic drain valve to G 1/2 and manual drain valve from G 3/4



Ieejas spiediens
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)
Vides temperatūra
Max. 50 °C
Vielas temperatūra
max. 50 °C
Caurplūde
At P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Iedarbības pakāpe
99.999 %
Poru attālums filtra elementā
0.01 μm
Korpuss
Die-cast zinc, painted silver
Caurplūdes vērtības mērījums
At P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	C mm	D mm	H mm	DN
K- 07 25 10 76	G 3/8	380	48.0	14.0	131.6	38.0	6
K- 07 25 10 83	G 3/4	7000	133.0	36.0	206.0	134.0	20
K- 07 25 10 86	G 1	7000	133.0	36.0	206.0	120.0	25