



Modelis
 Diaphragm pressure regulator with relieving, centrifugal filter
Vides temperatūra
 -10 °C to +50 °C
Vielas temperatūra
 -10 °C to +50 °C
Darba vides
 Saspiests gaiss
Filtra smalkums
 5.00 µm
maks. kondensāta daudzums
 49 cm³
Manometra pieslēgums
 G 1/4 i
Nominālā caurplūde G 1/2
 5.200 l/min (P1 = 10 bar, P2 = 6,3 bar/Delta P = 1 bar)
PE maks. 4
 Pa 0,5 - 8 bar (Standard)
Pa 0,1 - 1 bar
Pa 0,1 - 2 bar
Pa 0,2 - 4 bar
Pa 0,5 - 10 bar
Pa 0,5 - 16 bar
PE maks. 6
 16 bar
Nominālā caurplūde G 3/8
 4.300 l/min (P1 = 10 bar, P2 = 6,3 bar/Delta P = 1 bar)
Stiprinājuma veids
 Line mounting, panel mounting, mounting kit or wall mounting
Uzstādīšanas stāvoklis
 Vertical, drain down
Vadība/drošinātājs
 lockable handwheel
Filtra elements
 Cellpor
Korpuss
 PA66
Membrāna, blīvējumi
 Ms/NBR/PA6

Produkts

Apzīmējums	Filtra smalkums µm	PE maks. 6 bar	Savienojums	Regulēšanas diapazons	Indikācijas diapazoni	Tvertne	Tipizmērs	Kondensāts
K- 07 25 21 60	5.00	16	G 3/8 female	0.1 - 1 bar	0 - 1,6 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 61	5.00	16	G 3/8 female	0.1 - 2 bar	0 - 2,5 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 62	5.00	16	G 3/8 female	0.2 - 4 bar	0 - 6 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 63	5.00	16	G 3/8 female	0.5 - 8 bar	0 - 10 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 64	5.00	16	G 3/8 female	0.5 - 10 bar	0 - 16 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 65	5.00	16	G 3/8 female	0.5 - 16 bar	0 - 25 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 66	5.00	16	G 1/2 female	0.1 - 1 bar	0 - 1,6 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 67	5.00	16	G 1/2 female	0.1 - 2 bar	0 - 2,5 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 68	5.00	16	G 1/2 female	0.2 - 4 bar	0 - 6 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 69	5.00	16	G 1/2 female	0.5 - 8 bar	0 - 10 bar	polycarbonate with protective cage	2	manual / s automatic

Apzīmējums	Filtra smalkums µm	PE maks. 6 bar	Savienojums	Regulēšanas diapazons	Indikācijas diapazoni	Tvertne	Tipizmērs	Kondensāt
K- 07 25 21 70	5.00	16	G 1/2 female	0.5 - 10 bar	0 - 16 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 71	5.00	16	G 1/2 female	0.5 - 16 bar	0 - 25 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 72	5.00	16	G 3/8 female	0.1 - 1 bar	0 - 1,6 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 73	5.00	16	G 3/8 female	0.1 - 2 bar	0 - 2,5 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 74	5.00	16	G 3/8 female	0.2 - 4 bar	0 - 6 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 75	5.00	16	G 3/8 female	0.5 - 8 bar	0 - 10 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 76	5.00	16	G 3/8 female	0.5 - 10 bar	0 - 16 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 77	5.00	16	G 3/8 female	0.5 - 16 bar	0 - 25 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 78	5.00	16	G 1/2 female	0.1 - 1 bar	0 - 1,6 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 79	5.00	16	G 1/2 female	0.1 - 2 bar	0 - 2,5 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 80	5.00	16	G 1/2 female	0.2 - 4 bar	0 - 6 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 81	5.00	16	G 1/2 female	0.5 - 8 bar	0 - 10 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 82	5.00	16	G 1/2 female	0.5 - 10 bar	0 - 16 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 83	5.00	16	G 1/2 female	0.5 - 16 bar	0 - 25 bar	zinc with visual display	2	manual / s automatic