

K-FI REGL METALLBE MANO STANDARD-MI

HANSA FLEX
OFICIĀLĀ LATVIJAS PĀRSTĀVniecība

Filter regulators with metal bowl, incl. pressure gauge and panel nut



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Blīvējums
NBR
Poru attālums filtra elementā
5 µm
Atsperes korpuss
POM-brass
Korpuss
Die-cast zinc, painted silver
Drain valve
Semi-automatic for variant with polycarbonate bowl, Manual for variant with metal bowl
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Caurpl_de nom.
350 l/min

Apraksts

Compact, reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.
The pressure setting can be locked by pushing the knob down.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	A mm	B	C mm	D mm	DN
K- 07 25 06 65	G 1/8	0.5 - 10 bar	40.0	163.5 mm	65.0	98.5	5
K- 07 25 06 66	G 1/4	0.5 - 10 bar	40.0	163.5 mm	65.0	98.5	5