

K-FI REGL METALLBE MANO STANDARD-MI

Filter regulators with metal bowl, incl. pressure gauge and panel nut



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Blīvējums
NBR
Poru attālums filtra elementā
5 µm
Atsperes korpuss
POM-brass
Korpuss
Die-cast zinc, painted silver
Drain valve
Semi-automatic for variant with polycarbonate bowl, Manual for variant with metal bowl
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Caurpl_de nom.
350 l/min

Apraksts

Compact, reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.
The pressure setting can be locked by pushing the knob down.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	A mm	B	C mm	D mm	DN
K- 07 25 06 65	G 1/8	0.5 - 10 bar	40.0	163.5 mm	65.0	98.5	5
K- 07 25 06 66	G 1/4	0.5 - 10 bar	40.0	163.5 mm	65.0	98.5	5