

# K-FI REGL PC-BEHAEL MANO MULTIFIX M

Filter regulators with polycarbonate bowl and pressure gauge



Ieejas spiediens  
Max. 16 bar (also for metal tank!)

Vides temperatūra  
Max. 60 °C

Vielas temperatūra  
max. 60 °C

Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

Blīvējums  
NBR

Poru attālums filtra elementā  
5  $\mu\text{m}$

Atsperes korpuss  
POM-brass

Korpuss  
Die-cast zinc

Drain valve  
Semi-automatic

Caurplūdes vērtības mērījums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmērs
K- 07 25 00 63	G 1/8	0.1 - 3 bar	950	40.0	165.5 mm	63.0	102.5	5	0
K- 07 25 00 62	G 1/8	0.5 - 10 bar	950	40.0	165.5 mm	63.0	102.5	5	0
K- 07 25 00 65	G 1/4	0.1 - 3 bar	1100	40.0	165.5 mm	63.0	102.5	5	0
K- 07 25 00 66	G 1/4	0.5 - 10 bar	1100	40.0	165.5 mm	63.0	102.5	5	0