

K-FI REGL PC-BEHAEL S H ABL STANDAR

Filter regulators with polycarbonate bowl, bowl guard and semi-automatic drain valve



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)
Regulēšanas diapazons
0.5 to 10 bar (polycarbonate bowl), 0.5 to 16 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm (Size 1 / Size 3), 40 μm (Size 2 / Size 4)
Korpuss
Die-cast zinc (G1/4 to G1/2), silver painted; aluminium (G3/4 to G1), silver painted
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Caurpl_de nom. l/min | A mm | C mm | D mm | DN | F mm |
|----------------|--------|-------------------------|---------|---------|---------|----|---------|
| K- 07 25 06 68 | G 1/4 | 900 | 54.0 | 106.5 | 129.7 | 8 | 62.0 |
| K- 07 25 06 71 | G 3/8 | 900 | 54.0 | 106.5 | 129.7 | 8 | 62.0 |
| K- 07 25 06 74 | G 3/8 | 1500 | 70.0 | 120.5 | 145.9 | 11 | 76.5 |
| K- 07 25 06 78 | G 1/2 | 3000 | 82.0 | 130.0 | 169.4 | 14 | 83.0 |
| K- 07 25 06 81 | G 3/4 | 7000 | 125.0 | 190.6 | 261.4 | 25 | 145.0 |
| K- 07 25 06 84 | G 1 | 7000 | 125.0 | 190.6 | 261.4 | 25 | 145.0 |