

K-FI AK KOH 0 DIFFERENZ MANO

Activated carbon filters without differential pressure gauge



Ieejas spiediens
Min. 4 bar, Max. 16 bar
Diferenciālā spiediena manometra indikāciju diapazons
0 - 2 bar
Korpuss, filtra tvertne
Aluminium
Vides temperatūra
+5 °C to +60 °C
Filtra ieliktnis
Activated carbon
Atlikusi eļļa
0.005 mg/m³
Caurplūdes vērtības mērījums
At P1 = 6 bar and pressure drop Δp = 0.5%

Apraksts

Suitable for all applications where the standard centrifugal separators do not afford the desired efficiency. The pre-filters and micro-filters are equipped with an automatic drain valve. All devices can be supplied with or without a differential pressure gauge. The differential pressure gauge indicates the degree of contamination of the filter element as a function of the pressure drop.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B2 mm	C mm	D mm
K- 07 25 13 26	G 1/4	500	82.5	248.0	57.0	263.0
K- 07 25 13 27	G 3/8	500	82.5	248.0	57.0	263.0
K- 07 25 13 28	G 1/2	500	82.5	248.0	57.0	263.0
K- 07 25 13 29	G 3/4	1000	82.5	318.0	57.0	403.0
K- 07 25 13 30	G 1	1500	118.0	333.0	72.0	368.0
K- 07 25 13 31	G 1 1/4	2650	118.0	433.0	72.0	568.0
K- 07 25 13 32	G 1 1/2	4150	118.0	533.0	72.0	768.0
K- 07 25 13 33	G 2	6650	118.0	723.0	72.0	1148.0