



Modelis
Ieskrūvējami noslēgi ar ventilācijas filtru, bronza 40 µm
Ar blīvējumu
Temperatūras diapazons
no -20 °C līdz +100 °C
Materiāls
Tērauds

Apraksts

Piemērots lietošanai arī putekļainā vidē

Produkts

Apzīmējums	Vītne	A mm	B mm	SW mm	Ø D mm	Svars kg
HK TSF 1 G14	G 1/4"	17	8	17	17	0.01
HK TSF 2 G38	G 3/8"	19	10	22	22	0.03
HK TSF 3 G12	G 1/2"	21	12	27	26	0.04
HK TSF 4 G34	G 3/4"	24	14	32	30	0.06
HK TSF 5 G1	G 1"	29	16	40	38	0.08
HK TSF 6 G114	G 1,1/4"	33	16	50	50	0.10
HK TSF 7 G112	G 1,1/2"	35	16	55	55	0.12
HK TSF 8 G2	G 2"	40	16	70	70	0.14
HK TSF 1 M1415	M 14 x 1.5	17	8	17	17	0.01
HK TSF 2 M1615	M 16 x 1.5	19	10	22	22	0.03
HK TSF 3 M1815	M 18 x 1.5	19	10	22	22	0.04
HK TSF 4 M2015	M 20 x 1.5	21	12	24	24	0.06
HK TSF 5 M2215	M 22 x 1.5	21	12	27	26	0.06
HK TSF 6 M2420	M 24 x 2	24	12	30	30	0.10
HK TSF 7 M3020	M 30 x 2	25	14	36	30	0.12
HK TSF 8 M3320	M 33 x 2	29	16	40	38	0.14

SW = uzgriežņu atslēgas platums