



Standarts
SAE J 518 C
ISO 6162
ISO 6162
Konstrukcija
Taisna
Modelis
SAE gala plātne
Stiprinājums
Urbums skrūvei
Materiāls
Tērauds St 35
Virsmas aizsardzība
ieeļļošana ar melno eļļu

Produkts

Apzīmējums	Spiediena sērija	Tipizmērs	C mm	D mm	E mm	F mm	H mm	L mm
AP 80	3000 PSI	1/2"	38.1	54	17.5	45.6	3	9
AP 100	3000 PSI	3/4"	47.6	65	22.3	51.8	3	11
AP 102	3000 PSI	1"	52.4	70	26.2	58.4	3	11
AP 104	3000 PSI	1.1/4"	58.7	79	30.2	72.6	3	11
AP 106	3000 PSI	1.1/2"	69.9	94	35.7	82.2	3	13
AP 108	3000 PSI	2"	77.8	102	42.9	90.0	3	13
AP 110	3000 PSI	2.1/2"	88.9	114	50.8	108.1	3	13
AP 112	3000 PSI	3"	106.4	135	61.9	130.6	4	17
AP 114	3000 PSI	3.1/2"	120.7	152	69.9	139.0	4	17
AP 116	3000 PSI	4"	130.2	162	77.8	152.0	4	17
AP 118	3000 PSI	5"	152.4	184	92.1	180.0	4	17
AP 401	6000 PSI	1/2"	40.5	56	18.2	47.2	4	9
AP 402	6000 PSI	3/4"	50.8	71	23.8	60.0	4	11
AP 403	6000 PSI	1"	57.2	81	27.8	69.6	4	13
AP 404	6000 PSI	1.1/4"	66.7	95	31.8	77.2	4	15
AP 405	6000 PSI	1.1/2"	79.4	113	36.5	95.0	4	17
AP 406	6000 PSI	2"	96.8	133	44.5	113.8	4	21