

SFH (3000 / 6000 PSI) 4 L

VA

SAE atloka stiprinājums



Standarts
SAE J518
ISO 6162-1
ISO 6162-1/-2
Materiāls
Nerūsējošais tērauds

Norādīt

Ieteicamās skrūves ir norādītas ailēs M (metriskās) vai M (collu).

Produkts

Apzīmējums	Atloka izmērs	Spiediena sērija	PB 10.9 bar	A mm	B mm	C mm	D mm	E mm	F mm	L mm	M collas	M metr.
SFH 13 4 L VA	1/2"	3000 PSI	350	31.0	6.2	38.1	54	17.5	45.6	8.7	5/16" x 1.1/4"	M 8 x 25
SFH 20 4 L VA	3/4"	3000 PSI	350	38.9	6.2	47.6	65	22.2	51.8	10.7	3/8" x 1.1/4"	M 10 x 30
SFH 25 4 L VA	1"	3000 PSI	315	45.2	7.5	52.4	70	26.2	58.4	10.7	3/8" x 1.1/4"	M 10 x 30
SFH 32 4 L VA	1.1/4"	3000 PSI	250	51.6	7.5	58.7	79	30.2	72.6	12.0	7/16" x 1.1/2"	M 10 x 30
SFH 40 4 L VA	1.1/2"	3000 PSI	200	61.1	7.5	69.9	94	35.7	82.2	13.5	1/2" x 1.1/2"	M 12 x 35
SFH 50 4 L VA	2"	3000 PSI	200	72.2	9.0	77.8	102	42.9	93.4	13.5	1/2" x 1.1/2"	M 12 x 35
SFH 60 4 L VA	2.1/2"	3000 PSI	160	84.9	9.0	88.9	114	50.8	108.2	13.5	1/2" x 1.1/2"	M 12 x 40
SFH 75 4 L VA	3"	3000 PSI	160	102.4	9.0	106.4	135	61.9	130.6	17.0	5/8" x 2"	M 16 x 50
SFH6 13 4 L VA	1/2"	6000 PSI	400	32.5	7.2	40.5	56	18.2	47.2	8.7	5/16" x 1.1/4"	M 8 x 30
SFH6 20 4 L VA	3/4"	6000 PSI	400	42.1	8.3	50.8	71	23.8	60.0	10.7	3/8" x 1.1/2"	M 10 x 35
SFH6 25 4 L VA	1"	6000 PSI	400	48.4	9.0	57.2	81	27.8	69.9	13.0	-	M 12 x 45
SFH6 32 4 L VA	1.1/4"	6000 PSI	400	54.8	9.8	66.7	95	31.8	77.2	14.7	1/2" x 1.3/4"	M 14 x 45
SFH6 40 4 L VA	1.1/2"	6000 PSI	400	64.3	12.1	79.4	113	36.5	95.0	17.0	5/8" x 2"	M 16 x 55
SFH6 50 4 L VA	2"	6000 PSI	400	80.2	12.1	96.8	133	44.5	113.8	21.0	3/4" x 2.1/2"	M 20 x 70