

# K-ZFL ABSP-KLAPPEN DOPPEL

Butterfly valves, with double-acting actuator, min. pilot pressure 5 bar

**Modelis**

Pneumatic actuators, in double- or single acting version

**Darba vides**

Water / steam, salt water, salt water, ester, ketone, alkali, caustic soda, sodium hydroxide. Not recommended for hydrocarbons

**Ekspluatācijas spiediens**

Max. 16 bar

**Ekspluatācijas temperatūra**

-15 °C to +120 °C

**Regulēšanas spiediens**

5.5 bar

**Vārsta adapteris**

Supplied as standard, operated by a 3/2- or 5/2-way valve

**Griešanas leņķis**

90 °

**Korpuss**

Grey cast iron GG25 epoxy resin coated, RAL 5015

**Piedziņa**

aluminium eloxed

**Piedziņas blīvējums**

NBR

**Blīvējums**

EPDM

**Vārpsta**

SS416

**Vārpstas blīvējums**

EPDM

**Vadība**

Optional mittels 3/2- oder 5/2-Wegeventil oder Stellungsregler mit NAMUR-Anschluß

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Griešanas leņķis	Paplāksne	DN	B mm	H1 mm	H2 mm	H3 mm	L mm
K- 07 30 03 28	90	Stainless Steel CF8M/1.4404	40	38.0	68.0	108.0	212.0	94.0
K- 07 30 03 29	90	Stainless Steel CF8M/1.4404	50	47.0	71.0	143.0	247.0	100.0
K- 07 30 03 30	90	Stainless Steel CF8M/1.4404	65	49.0	78.0	155.0	259.0	115.0
K- 07 30 03 31	90	Stainless Steel CF8M/1.4404	80	47.0	89.0	162.0	280.0	127.0
K- 07 30 03 32	90	Stainless Steel CF8M/1.4404	100	56.0	102.0	178.0	308.0	163.0
K- 07 30 03 33	90	Stainless Steel CF8M/1.4404	125	59.0	123.0	191.0	321.0	190.0
K- 07 30 03 35	90	Stainless Steel CF8M/1.4404	150	59.0	138.0	205.0	352.0	216.0