

K-2-BK V DURCHG 20-63 INFI

2/2-way ball valve Ø 20 mm - Ø 63 mm full bore



Darba vides
Compressed air, vacuum, inert gases
Eksploatācijas spiediens
-0,99 bar - 15 bar
Temperatūras diapazons
-20 °C to +80 °C
Blīvgredzens
NBR
Blīvējums
NBR
Drošības gredzens
Technopolymer
Korpuss
Nickel-plated brass
Spīlgredzens
Stainless steel 1.4301
Uzgrieznis
Nickel-plated brass

Produkts

| Apzīmējums | Caurules ārējais Ø | B mm | C mm | DN | E mm | G mm | H mm | L mm | SW1 mm | SW2 mm |
|----------------|--------------------|---------|---------|----|---------|---------|---------|---------|-----------|-----------|
| K- 07 40 54 36 | 20 mm | 31.5 | 58.5 | 17 | 34.5 | 88 | 42.0 | 121.5 | 32 | 30 |
| K- 07 40 54 37 | 25 mm | 38.5 | 61.5 | 22 | 42.5 | 106 | 47.5 | 138.5 | 41 | 35 |
| K- 07 40 54 38 | 32 mm | 46.0 | 75.0 | 29 | 52.0 | 106 | 53.0 | 167.0 | 50 | 45 |
| K- 07 40 54 39 | 40 mm | 52.5 | 81.0 | 37 | 63.0 | 134 | 65.0 | 186.0 | 59 | 55 |
| K- 07 40 54 40 | 50 mm | 63.5 | 103.0 | 46 | 73.0 | 134 | 72.5 | 230.0 | 69 | 65 |