

K-BKR HANDHEBEL IG IG

Ball valves with hand lever, female/female thread



Pieteikums platība

Compressed air, water, non-toxic and neutral gases, heating oil (EL),(S), lubricants, diesel oil, water based coatings

Ekspluatācijas temperatūra

-20 °C to +130 °C

Vitnes apraksts

G thread acc. to DIN EN ISO 228-1, R thread acc. to DIN EN 10226 (ISO 7-1)

Korpuss

Nickel-plated brass

Lode

hardchrome-plated brass

Lodes blīvējums

PTFE

Svira

Alu, painted black

Vārpstas blīvējums

PTFE (politetrafluoretilēns)

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	DN	PN (bar)	Vitnes	A mm	B mm	E mm	F mm	L mm	SW mm
K- 07 30 21 19	8	80	G 1/4	75.0	51.5	6.5	6.5	40.5	18
K- 07 30 21 20	10	80	G 3/8	75.0	54.0	8.5	8.5	46.0	21
K- 07 30 21 21	15	80	G 1/2	100.0	64.0	9.5	9.5	55.0	26
K- 07 30 21 22	20	80	G 3/4	120.0	67.5	12.5	12.5	65.0	32
K- 07 30 21 23	25	80	G 1	120.0	80.0	13.5	13.5	76.0	39
K- 07 30 21 24	32	80	G 1 1/4	150.0	94.0	13.5	13.5	85.0	49
K- 07 30 21 25	40	80	G 1 1/2	150.0	103.0	18.0	18.0	103.0	56
K- 07 30 21 26	50	63	G 2	175.0	115.5	20.5	20.5	121.0	69
K- 07 30 21 27	65	40	G 2 1/2	280.0	152.0	24.2	24.2	148.0	85
K- 07 30 21 28	80	40	G 3	280.0	163.5	26.8	26.8	172.0	100