

# K-PROP VENTIL LU GA 24 V

## DC

Proportional valves for controlling the flow of air / gas, 24 VDC, closed when de-energised



Temperatūras diapazons  
Max. 50 °C (G 1/8), Max. 90 °C (G 1/4, G 3/8)  
Darba vides  
Air, neutral gases, water, oil  
Spiediena diapazons  
Vacuum (max. 8 bar)  
Vadība  
Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA  
Drošinātāja rīcība  
Tight closure in case of loss of voltage  
Iekšējās daļas  
Stainless steel  
Korpuss, vārsta ligzda  
Brass  
Vārsta disks  
FKM  
Blīvējums  
FKM

## Apraksts

Ever increasing requirements with regard to quality, precision, productivity, convenience, user friendliness and service represent tough challenges for industrial plant and production facilities. These challenges can only be mastered if physical quantities such as temperature, pressure, force, speed, torque, etc. are optimally adapted to the operating conditions of each installation. Stepless adjustment of these parameters is vital. <br>Proportional valves allow the medium to be varied as a function of an electronic input variable. <br>By linking these valves to the electronics, it is possible to improve their accuracy and broaden their range of applications. A pressure regulator, for instance, needs to be suitable for several pressure ranges without having to adjust the pressure manually. <br>Proportional valves control the output pressure in a closed control loop proportionally to the selected setpoint signal. This output pressure, in other words, is continually compared with the specified setpoint and automatically adjusted according to actual parameter values.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Savienojums	DN	maks. ekspluatācijas spiediena atšķirība bar	A mm	B	C mm
K- 07 25 09 91	G 1/4"	2	8	85.0	40.0 mm	95.0
K- 07 25 09 92	G 1/4"	3	4	85.0	40.0 mm	95.0
K- 07 25 09 93	G 3/8"	6	1	85.0	48.0 mm	97.0
K- 07 25 09 94	G 3/8"	7	1	85.0	48.0 mm	97.0