


Safety ball valve with spring return



Ekspluatācijas temperatūra  
-20 °C to +170 °C  
Vītnes apraksts  
Rp thread acc. to ISO 7-1  
Atspere  
Stainless steel 1.4301  
Korpuss  
Nickel-plated brass  
Lode  
hardchrome-plated brass  
Lodes blīvējums  
PTFE  
Svira  
Steel - PVC coated  
Vārpstas blīvējums  
FKM

## Apraksts

2/2-way safety ball valves, two parts, made of nickel-plated brass with spring return. Applications: Compressed air, water, oils, fuel oil, fuels, inert gases. Silicone-free. The ball valve is closed in the normal position and opens against spring force.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	DN	PN (bar)	Vītnes	A mm	B mm	L mm
K- 07 30 30 40	8	65	Rp 1/4	100.0	40.0	50.0
K- 07 30 30 43	10	65	Rp 3/8	100.0	40.0	60.0
K- 07 30 30 39	15	65	Rp 1/2	100.0	43.0	75.0
K- 07 30 30 42	20	40	Rp 3/4	120.0	51.0	80.0
K- 07 30 30 36	25	40	Rp 1	120.0	55.0	90.0
K- 07 30 30 38	32	40	Rp 1 1/4	158.0	75.0	110.0
K- 07 30 30 37	40	40	Rp 1 1/2	158.0	81.0	120.0
K- 07 30 30 41	50	40	Rp 2	158.0	88.0	140.0