

# K-S-BKR M ENTL-BOHR ABSCHL

Safety ball valves, lockable, with relief port



Atgaisošanas atvere  
M 5 (>1": Relief port G 1/4")  
Eksploatācijas temperatūra  
-10 °C to + 100 °C (depending on operating pressure)  
Vītnes apraksts  
Rp thread acc. to EN 10226  
Korpuss  
Nickel-plated brass  
Lode  
hardchrome-plated brass  
Lodes blīvējums  
PTFE  
Svira  
Steel - PVC coated  
Vārpstas blīvējums  
PTFE (politetrafluoretilēns)

## Apraksts

2/2-way safety ball valves, two parts, made of nickel-plated brass. Specially designed for pneumatic applications. <br>The valve shuts off the supply line and bleds the application area. Lockable hand lever in closed position.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	DN	PN (bar)	Vītnes	A mm	B mm	L mm
K- 07 30 29 29	8	14	Rp 1/4	96.0	49.0	45.0
K- 07 30 29 30	10	14	Rp 3/8	96.0	49.0	45.0
K- 07 30 29 31	15	14	Rp 1/2	96.0	51.0	59.0
K- 07 30 29 32	20	14	Rp 3/4	117.0	60.0	64.0
K- 07 30 29 33	25	14	Rp 1	117.0	64.0	81.0
K- 07 30 29 34	32	14	Rp 1 1/4	157.0	80.0	93.0
K- 07 30 29 35	40	14	Rp 1 1/2	157.0	86.0	102.0
K- 07 30 29 36	50	14	Rp 2	157.0	93.0	121.0