

K-S-BKR M ENTL-BOHR ABSCHL

Safety ball valves, lockable, with relief port



Atgaisošanas atvere
M 5 (>1": Relief port G 1/4")
Eksploatācijas temperatūra
-10 °C to + 100 °C (depending on operating pressure)
Vītnes apraksts
Rp thread acc. to EN 10226
Korpuss
Nickel-plated brass
Lode
hardchrome-plated brass
Lodes blīvējums
PTFE
Svira
Steel - PVC coated
Vārpstas blīvējums
PTFE (politetrafluoretilēns)

Apraksts

2/2-way safety ball valves, two parts, made of nickel-plated brass. Specially designed for pneumatic applications.
The valve shuts off the supply line and bleeds the application area. Lockable hand lever in closed position.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	DN	PN (bar)	Vītnes	A mm	B mm	L mm
K- 07 30 29 29	8	14	Rp 1/4	96.0	49.0	45.0
K- 07 30 29 30	10	14	Rp 3/8	96.0	49.0	45.0
K- 07 30 29 31	15	14	Rp 1/2	96.0	51.0	59.0
K- 07 30 29 32	20	14	Rp 3/4	117.0	60.0	64.0
K- 07 30 29 33	25	14	Rp 1	117.0	64.0	81.0
K- 07 30 29 34	32	14	Rp 1 1/4	157.0	80.0	93.0
K- 07 30 29 35	40	14	Rp 1 1/2	157.0	86.0	102.0
K- 07 30 29 36	50	14	Rp 2	157.0	93.0	121.0