

K-BKR STAN EIN FED VA

Stainless steel ball valves, single-acting actuator - spring to close



Modelis

Pneumatic actuators, in double- or single acting version, with integrated end-position feedback

Ekspluatācijas spiediens

max. 63 bar (depending on temperature and nominal size)

Ekspluatācijas temperatūra

-20 °C to +70°C

Griešanas leņķis

90 °

Normētas saskarnes

Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S

Regulēšanas spiediens

5.5 bar

Vārsta adapteris

Acc. to NAMUR

Lodveida krāna blīvējums

PTFE

Lodveida krāns

Stainless steel 1.4401, with ISO-flange plate

Piedziņa

aluminium eloxed

Piedziņas blīvējums

NBR

Apraksts

2-way cock, 3-piece, full bore

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Griešanas leņķis	DN	Vītnes	A mm	B mm	D mm	L mm	SW mm
K- 07 30 02 59	90	15	Rp 1/2	133.0	144.0	24.0	75.0	29
K- 07 30 02 60	90	15	Rp 1/2	116.0	135.0	24.0	75.0	29
K- 07 30 02 61	90	20	Rp 3/4	133.0	148.0	27.0	80.0	35
K- 07 30 02 62	90	25	Rp 1	137.0	170.0	33.0	90.0	41
K- 07 30 02 63	90	32	Rp 1 1/4	161.0	188.0	37.0	110.0	50
K- 07 30 02 64	90	40	Rp 1 1/2	180.0	198.0	40.0	120.0	58
K- 07 30 02 65	90	50	Rp 2	209.0	224.0	50.0	140.0	74
K- 07 30 02 66	90	65	Rp 2 1/2	221.0	268.0	60.0	185.0	85
K- 07 30 02 67	90	80	Rp 3	221.0	280.0	67.0	205.0	100