


# K-SSVKM NW 5 SCHL TUE MS BL

Quick disconnect couplings DN 5, brass with a bare metal surface, with bulkhead fitting and hose stem

**HANSA FLEX**  
OFICIĀLĀ LATVIJAS PĀRSTĀVniecība



Ekspluatācijas spiediens  
0 - 35 bar, maximum static working pressure (non-pulsating)  
Vielas temperatūra  
-20 °C to +100 °C  
Korpuss, uzmava, vārsta korpuss  
Brass  
Atspere, sprostgredzens, lodes  
Stainless steel  
Blīvējums  
NBR

## Apraksts

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Savienojums	Starpsienas vītnes	SW mm
K- 07 35 06 45	560	60.0	Stem, I.D. 4	M 10 x 1	14
K- 07 35 06 46	560	60.0	Stem, I.D. 6	M 12 x 1	17
K- 07 35 06 47	560	60.0	Stem, I.D. 9	M 12 x 1	17