


# K-SVKM NW 5 IG VA

Quick disconnect couplings DN 5, stainless steel 1.4305, female



Ekspluatācijas spiediens  
0 - 35 bar, maximum static working pressure (non-pulsating)  
Vielas temperatūra  
-15 °C to +200 °C  
Korpuss, uzdeva, vārsta korpuss  
Stainless steel 1.4305  
Atspere, sprostgredzens, lodes  
stain less steel  
Blīvējums  
FKM

## Apraksts

One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305, compact with a large bore. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory equipment, chemical applications, analysis and metering techniques.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Caurpl_de nom.<br>l/min | Garums<br>mm | Savienojums  | SW<br>mm |
|----------------|-------------------------|--------------|--------------|----------|
| K- 07 35 06 30 | 560                     | 36.0         | G 1/8 female | 14       |
| K- 07 35 06 31 | 560                     | 38.0         | G 1/4 female | 17       |
| K- 07 35 06 32 | 560                     | 38.0         | G 3/8 female | 19       |