


# K-SVKM NW 7,2 SCHL-TUE VA

Quick disconnect couplings DN 7.2, stainless steel, with hose stem



Ekspluatācijas spiediens  
1 - 35 bar and rough vacuum  
Vielas temperatūra  
-25 °C to +200 °C  
Korpuss, uzdeva, vārsta korpuss  
Stainless steel 1.4305  
Atspere, sprostgredzens  
Stainless steel 1.4310  
Fiksācijas tapas  
Stainless steel 1.4401  
Blīvējums  
FKM

## Apraksts

Classic standard coupling type, one side sealing, made of stainless steel. The closed sleeve protects the coupling from dirt. We recommend the use of stainless steel plugs and stems!

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Savienojums	SW mm
K- 07 35 07 65	1000	59.0	Stem, I.D. 6	22
K- 07 35 12 65	1000	59.0	Stem, I.D. 8	22
K- 07 35 07 66	1000	59.0	Stem, I.D. 9	22
K- 07 35 12 66	1000	59.0	Stem, I.D. 10	22
K- 07 35 07 67	1000	59.0	Stem, I.D. 13	22