


K-SVKM NW 7,8 SCHL TUE VA

Quick disconnect couplings DN 7.8, stainless steel 1.4305, with hose stem



Ekspluatācijas spiediens
0 - 35 bar, maximum static working pressure (non-pulsating)
Vielas temperatūra
-15 °C to +200 °C
Korpuss, uzmava, vārsta korpuss
Stainless steel 1.4305
Atspere, sprostgredzens, lodes
Stainless steel
Blīvējums
FKM

Apraksts

One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305. Ideal for: Pneumatic tools, laboratory equipment, chemical applications, instrumentation and control, safety systems, industrial plant engineering, mechanical engineering.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Savienojums	SW mm
K- 07 35 07 96	1800	73.5	Stem, I.D. 6	19
K- 07 35 07 97	1800	73.5	Stem, I.D. 8	19
K- 07 35 07 98	1800	73.5	Stem, I.D. 9	19
K- 07 35 07 99	1800	73.5	Stem, I.D. 10	19
K- 07 35 08 00	1800	73.5	Stem, I.D. 13	19