


K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8



Ekspluatācijas spiediens
0 - 35 bar, maximum static working pressure (non-pulsating)
Korpuss
Brass
Vielas temperatūra
-20 °C to +100 °C
Vārsts
Die-cast zinc, nickel-plated
Atbloķēšanas uzmava
Anodised aluminium
Atspere, sprostgredzens, lodes
stain less steel
Blīvējums
NBR

Apraksts

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Krāsa	Savienojums	SW mm
K- 07 35 08 01	1800	57.5	zaļš	G 1/4 male	19
K- 07 35 08 02	1800	57.5	zaļš	G 3/8 male	19
K- 07 35 08 03	1800	55.5	zaļš	G 1/4 female	19
K- 07 35 08 04	1800	54.5	zaļš	G 3/8 female	19
K- 07 35 08 05	1800	57.5	Brown	G 1/4 male	19
K- 07 35 08 06	1800	57.5	Brown	G 3/8 male	19
K- 07 35 08 07	1800	55.5	Brown	G 1/4 female	19
K- 07 35 08 08	1800	54.5	Brown	G 3/8 female	19
K- 07 35 08 09	1800	57.5	zils	G 1/4 male	19
K- 07 35 08 10	1800	57.5	zils	G 3/8 male	19
K- 07 35 08 11	1800	55.5	zils	G 1/4 female	19
K- 07 35 08 12	1800	54.5	zils	G 3/8 female	19
K- 07 35 08 13	1800	57.5	sarkans	G 1/4 male	19
K- 07 35 08 14	1800	57.5	sarkans	G 3/8 male	19
K- 07 35 08 15	1800	55.5	sarkans	G 1/4 female	19
K- 07 35 08 16	1800	54.5	sarkans	G 3/8 female	19