



Modelis
 Ātrā savienojuma uzdeva
 Savienojums 1
 BSP ārējā vītne, cilindriskā
 Eksploatācijas spiediens
 maks. 12 bar
 Savienojums 2
 Sleeve Ø 7.4 mm
 Iekšējās daļas
 Stainless steel
 Korpusa
 Aluminium, anodised
 Vielas temperatūra
 -20 °C to +70 °C
 Blīvējums
 NBR
 Vītne
 Nickel-plated brass
 Poga, vārsts
 Hardened, galvanised steel

Apraksts

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Caurpl_de nom. l/min	Savienojošās vītnes	Garums mm	Savienojums	SW mm
LKM 06 HR ST DK	1800	G 1/4" -19	70.5	G 1/4 male	21
LKM 10 HR ST DK	1800	G 3/8" -19	70.0	G 3/8 male	21
LKM 13 HR ST DK	1800	G 1/2" -14	72.5	G 1/2 male	25