



Modelis
Ātrā savienojuma uzdeva
Savienojums 1
BSP iekšējā vītne, cilindriska
Eksploatācijas spiediens
maks. 12 bar
Savienojums 2
Sleeve Ø 7.4 mm
Iekšējās daļas
Stainless steel
Korpuss
Aluminium, anodised
Vielas temperatūra
-20 °C to +70 °C
Blīvējums
NBR
Vītne
Nickel-plated brass
Poga, vārsts
Hardened, galvanised steel

Apraksts

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Caurpl_de nom. l/min	Savienojošās vītnes	Garums mm	Savienojums	SW mm
LKM 06 IR ST DK	1800	G 1/4" -19	71.5	G 1/4 female	21
LKM 10 IR ST DK	1800	G 3/8" -19	75.5	G 3/8 female	21
LKM 13 IR ST DK	1800	G 1/2" -14	77.5	G 1/2 female	24