



Modelis
Ātrā savienojuma uzmava
Savienojums 1
Šķūtenes savienojums
Ekspluatācijas spiediens
maks. 12 bar
Savienojums 2
Sleeve Ø 7.4 mm
Iekšējās dalas
Stainless steel
Korpuss
Aluminium, anodised
Vielas temperatūra
-20 °C to +70 °C
Blīvējums
NBR
Vitne
Nickel-plated brass
Poga, vārststs
Hardened, galvanised steel

Apraksts

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Caurpl_de nom. l/min	Šķūtenes ID mm	Garums mm	Savienojums	SW mm
LKM 06 MM ST DK	1800	6	88.5	Stem, I.D. 6	21
LKM 09 MM ST DK	1800	9	88.5	Stem, I.D. 9	21
LKM 13 MM ST DK	1800	13	88.5	Stem, I.D. 13	21