

Spraudsavienojuma uzdeva (gaiss) ar drošinātāju



Modelis  
 Ātrā savienojuma uzdeva  
 Savienojums 1  
 Šļūtenes savienojums  
 Eksploatācijas spiediens  
 maks. 12 bar  
 Savienojums 2  
 Sleeve Ø 7.4 mm  
 Iekšējās daļas  
 Stainless steel  
 Korpusa  
 Aluminium, anodised  
 Vielas temperatūra  
 -20 °C to +70 °C  
 Blīvējums  
 NBR  
 Vītne  
 Nickel-plated brass  
 Poga, vārsts  
 Hardened, galvanised steel

## Apraksts

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums      | Caurpl_de nom.<br>l/min | šļūtenes ID | Garums<br>mm | Savienojums   | SW<br>mm |
|-----------------|-------------------------|-------------|--------------|---------------|----------|
| LKM 06 MM ST DK | 1800                    | 6           | 88.5         | Stem, I.D. 6  | 21       |
| LKM 09 MM ST DK | 1800                    | 9           | 88.5         | Stem, I.D. 9  | 21       |
| LKM 13 MM ST DK | 1800                    | 13          | 88.5         | Stem, I.D. 13 | 21       |