



Ekspluatācijas spiediens  
maks. 20 bar  
Vielas temperatūra  
-20 °C to +100 °C  
Atspere, lodes  
Stainless-steel  
Bīdāma uzmava  
Anodised aluminium  
Vārsta korpusa pieslēgums  
Nickel-plated brass  
Atbloķēšanas uzmava  
Hardened and nickel-plated steel  
Blīvējums  
NBR

## Apraksts

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Caurpl_de nom.<br>l/min | Garums<br>mm | Savienojums   |
|----------------|-------------------------|--------------|---------------|
| K- 07 35 08 88 | 1400                    | 86.0         | Stem, I.D. 6  |
| K- 07 35 12 96 | 1400                    | 86.0         | Stem, I.D. 8  |
| K- 07 35 08 89 | 1400                    | 86.0         | Stem, I.D. 9  |
| K- 07 35 12 97 | 1400                    | 86.0         | Stem, I.D. 10 |
| K- 07 35 08 90 | 1400                    | 86.0         | Stem, I.D. 13 |