

# K-DMUF 1

Pressure transmitters (CrNi steel 1.4404)



Tips  
A-10  
Spriegums  
8 - 30 V  
Aizsardzības veids  
IP 65 acc. to EN 60529  
Elektriskais pieslēgums  
With right-angle connector acc. to DIN EN 175301-803 A  
Izejas signāls  
4 to 20 mA, 2-wire  
Nelinearitāte  
0.5% of span  
Vides temperatūra  
0 °C to +80 °C  
Vielas temperatūra  
0 °C to +80 °C  
Daļas, kas saskaras ar mērišanas vielu  
CrNi steel 1.4404  
Korpuss  
CrNi steel 1.4404

## Apraksts

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Mērišanas diapazons	Vītnes
K- 07 20 10 46	0 - 1.0 bar	G 1/4
K- 07 20 10 47	0 - 1.6 bar	G 1/4
K- 07 20 10 48	0 - 2.5 bar	G 1/4
K- 07 20 10 49	0 - 4.0 bar	G 1/4
K- 07 20 10 50	0 - 6.0 bar	G 1/4
K- 07 20 10 51	0 - 10.0 bar	G 1/4
K- 07 20 10 52	0 - 16.0 bar	G 1/4
K- 07 20 10 53	0 - 25.0 bar	G 1/4
K- 07 20 10 54	0 - 40.0 bar	G 1/4
K- 07 20 10 55	0 - 60.0 bar	G 1/4
K- 07 20 10 56	0 - 100.0 bar	G 1/4
K- 07 20 10 57	0 - 160.0 bar	G 1/4
K- 07 20 10 58	0 - 250.0 bar	G 1/4
K- 07 20 10 59	0 - 400.0 bar	G 1/4
K- 07 20 10 60	0 - 600.0 bar	G 1/4