



Tips  
S-20  
Spriegums  
DC 8 ... 36 V  
Aizsardzības veids  
IP 65 acc. to EN 60529  
Elektriskais pieslēgums  
With right-angle connector acc. to DIN EN 175301-803 A  
Izejas signāls  
4 to 20 mA, 2-wire  
Nelinearitāte  
up to 0.25% of span  
Vides temperatūra  
-40 °C to +70 °C  
Vielas temperatūra  
-30 °C to +100 °C  
Daļas, kas saskaras ar mērišanas vielu  
CrNi steel 1.4571  
Korpuss  
CrNi steel 1.4571

## Apraksts

Pressure transmitters, very high precision, in CrNi steel, for complex measurement tasks in the process industry as well as research and development.

Applications: Low temperature or outdoor applications, extreme shock loads and vibration levels, corrosive media in the chemical industry. Compatible with all internationally established process connections.

## Produkts

Apzīmējums	Mērišanas diapazons	Vītnes
K- 07 20 12 55	-1 / 0.0 bar	G 1/2
K- 07 20 12 56	0 - 0.4 bar	G 1/2
K- 07 20 12 57	0 - 1.0 bar	G 1/2
K- 07 20 12 64	0 - 4.0 bar	G 1/2
K- 07 20 12 67	0 - 6.0 bar	G 1/2
K- 07 20 12 58	0 - 10.0 bar	G 1/2
K- 07 20 12 60	0 - 16.0 bar	G 1/2
K- 07 20 12 62	0 - 25.0 bar	G 1/2
K- 07 20 12 65	0 - 40.0 bar	G 1/2
K- 07 20 12 68	0 - 60.0 bar	G 1/2
K- 07 20 12 59	0 - 100.0 bar	G 1/2
K- 07 20 12 61	0 - 160.0 bar	G 1/2
K- 07 20 12 63	0 - 250.0 bar	G 1/2
K- 07 20 12 66	0 - 400.0 bar	G 1/2
K- 07 20 12 69	0 - 600.0 bar	G 1/2