



Modelis  
Spring-loaded diaphragm (NBR); Spring-loaded piston; (10 to 70 bar versions)  
Pieteikums platība  
Air, hydraulic oil, oil emulsions, water  
Vides temperatūra  
-25 °C to +85 °C  
Elektriskais pieslēgums  
Tab connectors 2 x 6.3 x 0.8  
Slēgšanas biežums  
200/min.  
Slēgšanas spriegums  
42 V  
Materiāls  
Galvanised steel

## Apraksts

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Funkcija	Iestatišanas diapazons
K- 07 30 24 94	G 1/8	closer	0,3 - 2,0 bar
K- 07 30 24 95	G 1/8	closer	1,0 - 10,0 bar
K- 07 30 24 96	G 1/8	closer	10,0 - 70,0 bar
K- 07 30 24 97	G 1/4	closer	0,3 - 2,0 bar
K- 07 30 24 98	G 1/4	closer	1,0 - 10,0 bar
K- 07 30 24 99	G 1/4	closer	10,0 - 70,0 bar
K- 07 30 24 10	G 1/8	opener	0,3 - 2,0 bar
K- 07 30 24 11	G 1/8	opener	1,0 - 10,0 bar
K- 07 30 24 12	G 1/8	opener	10,0 - 70,0 bar
K- 07 30 24 13	G 1/4	opener	0,3 - 2,0 bar
K- 07 30 24 14	G 1/4	opener	1,0 - 10,0 bar
K- 07 30 24 15	G 1/4	opener	10,0 - 70,0 bar